

STIKO Deadweight Tester - DOS 0015

accuracy 0,015%

LOW
PISTON

Range (bar)	Interval	Range (psi)	Interval
0,5- 30 bar	0,05 bar	10- 500 psi	1 psi
0,5- 40 bar	0,05 bar	10- 650 psi	1 psi
0,5- 50 bar	0,05 bar	10- 800 psi	1 psi
0,5- 60 bar	0,05 bar	10-1000 psi	1 psi
0,5- 70 bar	0,05 bar	10-1100 psi	1 psi
0,5- 80 bar	0,05 bar	10-1250 psi	1 psi
0,5- 90 bar	0,05 bar	10-1400 psi	1 psi
0,5-100 bar	0,05 bar	10-1550 psi	1 psi
0,5-110 bar	0,05 bar	10-1700 psi	1 psi
0,5-120 bar	0,05 bar	10-1850 psi	1 psi
0,5-130 bar	0,05 bar	10-2000 psi	1 psi
0,5-140 bar	0,05 bar		

*A pleasure
to measure!*



MEDIUM
PISTON

Range (bar)	Interval	Range (psi)	Interval
5-150 bar	0,5 bar	100- 3000 psi	10 psi
5-200 bar	0,5 bar	100- 4000 psi	10 psi
5-250 bar	0,5 bar	100- 5000 psi	10 psi
5-300 bar	0,5 bar	100- 6000 psi	10 psi
5-350 bar	0,5 bar	100- 7000 psi	10 psi
5-400 bar	0,5 bar	100- 8000 psi	10 psi
5-450 bar	0,5 bar	100- 9000 psi	10 psi
5-500 bar	0,5 bar	100-10000 psi	10 psi
5-550 bar	0,5 bar		
5-600 bar	0,5 bar		
5-650 bar	0,5 bar		
5-700 bar	0,5 bar		

HIGH
PISTON

Range (bar)	Interval	Range (psi)	Interval
20- 700 bar	1 bar	200-10000 psi	20 psi
20- 800 bar	1 bar	200-11000 psi	20 psi
20- 900 bar	1 bar	200-12500 psi	20 psi
20-1000 bar	1 bar	200-14000 psi	20 psi
20-1100 bar	1 bar	200-15500 psi	20 psi
20-1200 bar	1 bar	200-17000 psi	20 psi
20-1300 bar	1 bar	200-18500 psi	20 psi
20-1400 bar	1 bar	200-20000 psi	20 psi



MEETAPPARATENFABRIEK BV

P.O. Box 46 - NL-9300 AA Roden
 Industrieweg 5 - NL-9301 LM Roden
 THE NETHERLANDS
 Telephone: +31-50-5013813
 Telefax: +31-50-5013824
 E-Mail: sales@stiko.nl
 Internet: www.stiko.nl